

**Tools required:** stud finder, pencil, tape measure, level, drill (6mm bit), 10mm ratchet or key wrench  
*Accessories mounted on drywall need to be firmly anchored or they will eventually loosen.*

**1. Position the accessory at the desired height** and then use an electronic stud finder to locate studs in the area.  
If installation on a stud(s) is not possible, install drywall plug(s) for mounting brackets.  
If possible, position the accessory so at least one mounting screw can go into a stud.

**2. Trace the accessory mounting hole(s) onto the wall.**

**3. Measure the centre to centre distance to second bracket.** Use a level to confirm the plane between both brackets.

**4. Trace the mounting hole(s).**

**5. Drill or punch appropriate-sized holes for either screws/bolts or wall plugs.**

*When template provided, print on legal paper size (8½ x 14) and **DO NOT SCALE.**  
Print settings include **PRINT ACTUAL SIZE.***

Paper Size: 8.5” x 14” (Legal)

**Anchoring for Additional Support**

Please note that some accessories in the LaLOO offering specifically require support backing.  
Install a 2x4 brace (or a 2x6 brace for grab bar installation) between studs at the predetermined desired height of the accessory.



**Anchoring in Tile**

Use tubular plastic anchors (not provided) to hold accessories firmly in place when installing into tile affixed to concrete backer board.  
Use a carbide glass/ tile bit to drill pilot holds.  
Tap in the anchors and fasten the mounting bracket with screws.  
(Use tapered anchors for tile installed on drywall.)



267mm  
10 1/2"

233mm  
9 1/8"



**Level Line**

**LaLOO**  
**ACCESSORIES**

Pilot Hole Template for  
**2602 Decorative Grab Bar**

**Verify all dimensions on template before installation.**  
Dimensions may vary +/- 3mm.